

获取被踢出用户列表信息

接口URL

http://api.polyv.net/live/v3/channel/chat/list-kicked

接口说明

- 1、作用：获取聊天室某个房间号的被踢出用户列表，列表中有踢出ip或踢出用户userid。

2、接口支持https协议

支持格式

JSON

请求方式

POST

请求参数

参数名	必选	类型	说明
channelId	是	string	频道号\房间号

响应成功JSON示例

```
{
  "code": 200,
  "status": "success",
  "message": "",
  "data": [
    {
      "banned": false,
      "channelId": "329298",
      "clientId": "61.144.144.182",
      "nick": "123",
      "pic": "//lvestatic.videooc.net/assets/wimages/missing_face.png",
      "roomId": "329298",
      "type": "userId",
      "uid": "dvaQMR0iTWv2TYumAABO",
      "userId": "1562134139532",
      "userType": "student"
    }
  ]
}
```

响应失败JSON示例：

未输入appId

```
{
  "code": 400,
  "status": "error",
  "message": "appId is required.",
  "data": ""
}
```

appId不正确

```
{
  "code": 400,
  "status": "error",
  "message": "application not found.",
  "data": ""
}
```

时间戳错误

```
{
  "code": 400,
  "status": "error",
  "message": "invalid timestamp.",
  "data": ""
}
```

签名错误

```
{
  "code": 403,
  "status": "error",
  "message": "invalid signature.",
  "data": ""
}
```

字段说明

参数名	说明
code	响应代码，成功为200，失败为400，签名错误为401，异常错误500
status	成功为success，失败为error
message	错误时为错误提示消息
channelId	频道号
clientIp	用户Ip
nick	昵称
pic	头像
roomId	房间号
type	被踢出类型
uid	socketId
userId	用户userId
userType	用户类型：teacher、student等

php请求示例

```
?php
//引用config.php
include 'config.php';

$params = array(
    'appId' => $appId,
    'timestamp' => $timestamp,
    'channelId' => $channelId
);

//生成sign
$sign = getSign($params); //详细查看config.php文件的getSign方法
$params['sign'] = $sign;

$url = "http://api.polyv.net/live/v3/channel/chat/list-kicked?".http_build_query($params);

$curl = curl_init();
curl_setopt($curl, CURLOPT_RETURNTRANSFER, true);
curl_setopt($curl, CURLOPT_TIMEOUT, 500);
curl_setopt($curl, CURLOPT_URL, $url);
curl_setopt($curl, CURLOPT_POST, 0);
$res = curl_exec($curl);
curl_close($curl);

echo $res;

?>
```